

INTERNATIONAL SEARCH REPORT

International application No.

PCT/SE 97/00895

A. CLASSIFICATION OF SUBJECT MATTER

IPC6: H02K 1/20, H02K 3/40, H02K 15/08

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC6: H02K

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

SE,DK,FI,NO classes as above

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

WPI

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	US 5036165 A (R.K. ELTON ET AL), 30 July 1991 (30.07.91), see the whole document --	1-2,21-23
Y	US 4853565 A (R.K.ELTON), 1 August 1989 (01.08.89), column 5, line 55 - line 61; column 7, line 12 - line 37, figures 4,7 --	1-2,21-23
Y	US 4208597 A (A.MULACH ET AL.), 17 June 1980 (17.06.80), see the whole document	1-2,21-23
X		10-20
A		3,4-9
	--	

☒ Further documents are listed in the continuation of Box C.☒ See patent family annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

29 Sept 1997

Date of mailing of the international search report

07-10- 1997

Name and mailing address of the ISA/
Swedish Patent Office
Box 5055, S-102 42 STOCKHOLM

Authorized officer

Lars Jakobsson

INTERNATIONAL SEARCH REPORT

International application No.

PCT/SE 97/00895

C (Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	US 5365132 A (J.C.HANN ET AL), 15 November 1994 (15.11.94), se the whole document	1-2,21-23
X		10-20
A		3,4-9
	--	
Y	US 4745314 A (J.NAKANO), 17 May 1988 (17.05.88)	1-2,21-23
X		10-20
A		3,4-9
	--	
A	EP 0684682 A1 (GEC ALSTHOM LTD.), 29 November 1995 (29.11.95), see the whole document	4-9
	--	
A	US 3801843 A (J.C.CORMAN ET AL), 2 April 1974 (02.04.74), see the whole document	4-9
	-- -----	

INTERNATIONAL SEARCH REPORT

International application No.

PCT/SE 97/00895

Box I Observations where certain claims were found unsearchable (Continuation of Item 1 of first sheet)

This international search report has not been established in respect of certain claims under Article 17(2)(a) for the following reasons:

1. ☐ Claims Nos.:
because they relate to subject matter not required to be searched by this Authority, namely:
2. ☐ Claims Nos.:
because they relate to parts of the international application that do not comply with the prescribed requirements to such an extent that no meaningful international search can be carried out, specifically:
3. ☐ Claims Nos.:
because they are dependent claims and are not drafted in accordance with the second and third sentences of Rule 6.4(a).

Box II Observations where unity of invention is lacking (Continuation of Item 2 of first sheet)

This International Searching Authority found multiple inventions in this international application, as follows:

Claim 1: An electric machine comprising a winding with semiconducting layers and a clamping device.

Claim 4: An electric machine with a cooling tube in a stator tooth where the cooling tube is connected to a clamping means.

Claim 10: An electric machine with a clamping device.

Claims 4 and 10 have no special technical features in common.

1. ☐ As all required additional search fees were timely paid by the applicant, this international search report covers all searchable claims.
2. ☒ As all searchable claims could be searched without effort justifying an additional fee, this Authority did not invite payment of any additional fee.
3. ☐ As only some of the required additional search fees were timely paid by the applicant, this international search report covers only those claims for which fees were paid, specifically claims Nos.:
4. ☐ No required additional search fees were timely paid by the applicant. Consequently, this international search report is restricted to the invention first mentioned in the claims; it is covered by claims Nos.:

Remark on Protest

- ☐ The additional search fees were accompanied by the applicant's protest.
☐ No protest accompanied the payment of additional search fees.

INTERNATIONAL SEARCH REPORT
Information on patent family members

01/09/97

International application No.
PCT/SE 97/00895

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 5036165 A	30/07/91	US 5066881 A US 5067046 A CA 1245270 A US 4853565 A	19/11/91 19/11/91 22/11/88 01/08/89
US 4853565 A	01/08/89	CA 1245270 A US 5036165 A US 5066881 A US 5067046 A	22/11/88 30/07/91 19/11/91 19/11/91
US 4208597 A	17/06/80	BE 877203 A CA 1083212 A DE 2924697 A FR 2429513 A JP 55005095 A	24/12/79 05/08/80 10/01/80 18/01/80 14/01/80
US 5365132 A	15/11/94	CA 2122386 A EP 0627804 A JP 7023538 A	28/11/94 07/12/94 24/01/95
US 4745314 A	17/05/88	JP 61121729 A WO 8603069 A	09/06/86 22/05/86
EP 0684682 A1	29/11/95	CA 2148213 A FI 952501 A GB 2289992 A GB 9410351 D JP 7322565 A	25/11/95 25/11/95 06/12/95 00/00/00 08/12/95
US 3801843 A	02/04/74	CA 964710 A DE 2330172 A FR 2189915 A,B	18/03/75 03/01/74 25/01/74

PCT

INTERNATIONAL PRELIMINARY EXAMINATION REPORT

(PCT Article 36 and Rule 70)

Applicant's or agent's file reference P 97-124/AE/PA	FOR FURTHER ACTION See Notification of Transmittal of International Preliminary Examination Report (Form PCT/IPEA/416)	
International application No. PCT/SE97/00895	International filing date (day/month/year) 27.05.1997	Priority date (day/month/year) 29.05.1996
International Patent Classification (IPC) or national classification and IPC ₆ H 02 K 1/20, H 02 K 3/40, H 02 K 15/08		
Applicant Asea Brown Boveri AB et al.		

1. This international preliminary examination report has been prepared by this International Preliminary Examining Authority and is transmitted to the applicant according to Article 36.

2. This REPORT consists of a total of 4 sheets, including this cover sheet.

☒ This report is also accompanied by ANNEXES, i.e., sheets of the description, claims and/or drawings which have been amended and are the basis for this report and/or sheets containing rectifications made before this Authority (see Rule 70.16 and Section 607 of the Administrative Instructions under the PCT).

These annexes consist of a total of 3 sheets.

3. This report contains indications relating to the following items:

- I ☒ Basis of the report
- II ☐ Priority
- III ☐ Non-establishment of opinion with regard to novelty, inventive step and industrial applicability
- IV ☐ Lack of unity of invention
- V ☒ Reasoned statement under Article 35(2) with regard to novelty, inventive step or industrial applicability; citations and explanations supporting such statement
- VI ☐ Certain documents cited
- VII ☐ Certain defects in the international application
- VIII ☐ Certain observations on the international application

Date of submission of the demand 19.12.1997	Date of completion of this report 02.10.1998
Name and mailing address of the IPEA/SE Patent- och registreringsverket Box 5055 S-102 42 STOCKHOLM Facsimile No. 08-667 72 88	Authorized officer Lars Jakobsson Telephone No. 08-782 25 00

INTERNATIONAL PRELIMINARY EXAMINATION REPORT

International application No.

PCT/SE97/00895

V. Reasoned statement¹ under Article 35(2) with regard to novelty, inventive step or industrial applicability; citations and explanations supporting such statement

1. Statement

Novelty (N)	Claims	<u>1-22</u>	YES
	Claims		NO
Inventive step (IS)	Claims	<u>1-22</u>	YES
	Claims		NO
Industrial applicability (IA)	Claims	<u>1-22</u>	YES
	Claims		NO

2. Citations and explanations

Documents cited in the International Search Report:

- (A) US 5036165
- (B) US 4853565
- (C) US 4208597
- (D) US 5365132
- (E) US 4745314
- (F) EP 0684682
- (G) US 3801843

The invention relates to a high-voltage rotating electric machine. The winding of the machine is provided with an insulation system comprising two semiconducting layers with solid insulation in-between and a clamping device pressing a packet of sheets together. The invention also relates to a rotating electric machine with a high-voltage cable and a cooling tube connected to a clamping means.

(A) describes a cable provided with two semiconducting layers with insulation there between. The semiconducting layers include pyrolyzed organic material and glass fibre. In this document it is suggested that the invented semiconducting layer can be applied to insulated conductors such as a winding in a dynamo-electric machine.

(B) is a document related by reference to document (A) and illustrate a semiconducting layer in intimate contact on an outer or inner surface of an insulation on a conventional winding in an electric machine. This document also describes the cable as in document (A).

(C) - (G) describes cooling arrangements for rotating electric machines.

.../...

INTERNATIONAL PRELIMINARY EXAMINATION REPORT

International application No.

PCT/SE97/00895

Supplemental Box

(To be used when the space in any of the preceding boxes is not sufficient)

Continuation of: Box V.

The claimed invention differs from the cited art in that the winding of the machine is provided with an insulation system comprising two semiconducting layers with solid insulation-between. The claimed invention (claims 4-9) also differs from the cited art in that a cooling tube is connected to a clamping means.

Even though it is suggested in document (A) to apply a semiconducting layer to a winding in a dynamo-electric machine there is no specific indication of using the disclosed cable in a dynamo-electric machine. Further investigating US 4853565, incorporated by reference in document (A), the skilled person will find it evident that the invented semiconducting layer is intended to be used on a conventional winding in a machine or in a cable. there is no proposal to use the cable with the insulating system as a winding in an electric machine. Nor can it be considered obvious to a person skilled in the art to use such a cable in a dynamo-electric machine since at the time of the invention it was not known to use a cable with solid insulation as a winding in an electrical machine and there is no teaching in prior art as a whole that would lead the skilled person to the claimed invention.

Accordingly, the invention claimed is novel and involves an inventive step. The invention is industrially applicable.

AMENDED CLAIMS

29-09-1998

1. A high-voltage rotating electric machine, comprising a magnetic core built by laminated steel and a winding placed in slots in the core of laminated steel, characterized in that the winding comprises an insulation system including at least two semiconducting layers, each layer constituting essentially an equipotential surface and also including solid isolation disposed therebetween and that a clamping device is extending axially from the laminated steel and arranged for holding a packet of sheets together and whereby at least one end of the core of the laminated steel is connected to at least one clamping device for axially pressing a packet of sheets together at a predetermined amount of tension.
2. A machine as claimed in claim 1, characterized in that the clamping device is extending axially through the magnetic core.
3. A machine as claimed in any of claim 1-2, characterized in that the axially extending clamping device is arranged with an inner space for circulating coolant.
4. A rotating electric machine, comprising a stator (1) wound with high-voltage cable and provided with stator teeth (4) extending radially inwards from an outer yoke portion (23), characterized in that at least one stator tooth (4) in a tooth sector (18) is provided with at least one axially-running cooling duct (24) connected to a cooling circuit (25) in which coolant is arranged to circulate and in that the axially-running cooling tube (24) is connected at least at one end of the stator (1) to a clamping means (27, 28) for axial compression of the stator (1).
5. A machine as claimed in claim 4, characterized in that the clamping means (27, 28) comprises at least one screw joint arranged, with the cooling tube (24), to axially clamp the laminations together.
6. A machine as claimed in either of claims 4 or 5, characterized in that at one side of the stator (1) the cooling tube (24) is provided with a firmly secured shoulder (32) and at the other side of the stator it is provided with a clamping means (27, 28) to axially clamp the stator laminations together.

7. A machine as claimed in claim 6, characterized in that the clamping means (27, 28) also acts against a pressure finger (19) for axial clamping of the stator laminations.

5 8. A machine as claimed in claim 7, characterized in that the clamping means (27, 28) is electrically insulated from the stator core (3).

9. A machine as claimed in claim 8, characterized in that the cooling tubes (24) are glued to the stator core (3).

10

10. A rotating electric machine comprising a wound stator (1) consisting of stator laminations and provided with stator teeth (104) extending radially inwards from an outer yoke portion (123), characterized in that the windings comprise a first semiconducting layer (13) around which layer an insulating layer (14) is arranged and a second semiconducting layer (15) arranged
15 around the insulating layer (14), and that an axially running clamping device electrically insulated from the stator laminations is connected at least at one end of the stator (1) to at least one clamping device (126) for axial compression to predetermined pre-stressing of the stator (1).

20

11. A machine as claimed in claim 10, characterized in that the stator winding consists of high-voltage cable (11).

12. A machine as claimed in either of claims 10 or 11, characterized
25 in that the clamping device (126) runs axially through the magnetic material of the stator (1).

13. A machine as claimed in either of claims 10 or 11, characterized
30 in that the clamping device (126) runs between the high-voltage cables (11) in the space (107) formed between two adjacent stator teeth (104).

14. A machine as claimed in any of claims 10-13, characterized in
that the entire clamping device (126) is made of an insulating material, preferably glass fibre.

35

15. A machine as claimed in any of claims 10-13, characterized in
that the clamping device (126) is arranged as a metallic pipe electrically insulated from the laminations of the stator (1).

16. A machine as claimed in either of claims 14 or 15, characterized in that the clamping device (126) is arranged to pre-stress the stator (1) with at least one spring device (129).
- 5 17. A machine as claimed in either of claims 14 or 15, characterized in that the clamping device (126) is arranged to pre-stress the laminated stack against the action of a rubber spring.
- 10 18. A machine as claimed in any of claims 10-17, characterized in that several clamping devices (126) are arranged in at least one stator tooth (104) so that each cooling tube (124) is flanked by an axially extending clamping device (126).
- 15 19. A machine as claimed in any of claims 10-18, characterized in that an additional clamping device (126) also runs through the yoke portion (123).
- 20 20. A machine as claimed in any of claims 10-19, characterized in that clamping devices (126) and cooling tubes (124) are arranged radially aligned.
- 25 21. A machine as claimed in any of claims 1-3, characterized in that at least one of the layers has substantially the same coefficient of thermal expansion as the solid insulation.
- 30 22. A machine as claimed in any of the preceding claims, characterized in that said winding is formed of a cable comprising one or more current-carrying conductors, each conductor having a number of strands, an inner semiconducting layer provided around each conductor, an insulating layer of solid insulating material provided around said inner semiconducting layer, and an outer semiconducting layer provided around said insulating layer.
-

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : H02K 1/20, 3/40, 15/08	A1	(11) International Publication Number: WO 97/45916
		(43) International Publication Date: 4 December 1997 (04.12.97)

(21) International Application Number: PCT/SE97/00895
(22) International Filing Date: 27 May 1997 (27.05.97)

(30) Priority Data:
9602079-7 29 May 1996 (29.05.96) SE
9602089-6 29 May 1996 (29.05.96) SE
9700351-1 3 February 1997 (03.02.97) SE

(71) Applicant (for all designated States except US): ASEA
BROWN BOVERI AB [SE/SE]; S-721 83 Västerås (SE).

(72) Inventors; and

(75) Inventors/Applicants (for US only): LEIJON, Mats [SE/SE];
Hyvlargatan 5, S-723 35 Västerås (SE). LARSSON, Bertil
[SE/SE]; Sammettsvägen 12, S-724 76 Västerås (SE). KY-
LANDER, Gunnar [SE/SE]; Stentorpsgatan 16 A, S-723
43 Västerås (SE). BERGGREN, Sören [SE/SE]; Vetter-
storpsgatan 30, S-724 62 Västerås (SE). ROTHMAN, Bengt
[SE/SE]; Profilgatan 16, S-723 36 Västerås (SE). JONAS,
Ivan [SE/SE]; Hermods väg 9, S-723 55 Västerås (SE). ED-
HAN, Anne [SE/SE]; Gudrunsväg 12, S-723 55 Västerås
(SE). HYLANDER, Jonny [SE/SE]; Öjenås, S-510 13
Björketorp (SE).

(74) Agent: EMTEDAL, Artur; L.A. Groth & Co. KB, P.O. Box
6107, S-102 32 Stockholm (SE).

(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR,
BY, CA, CH, CN, CU, CZ, CZ (Utility model), DE, DE
(Utility model), DK, DK (Utility model), EE, ES, FI, FI
(Utility model), GB, GE, GH, HU, IL, IS, JP, KE, KG,
KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG,
MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE,
SG, SI, SK, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU,
ARIPO patent (GH, KE, LS, MW, SD, SZ, UG), Eurasian
patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European
patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT,
LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI,
CM, GA, GN, ML, MR, NE, SN, TD, TG).

Published


With international search report.

Before the expiration of the time limit for amending the
claims and to be republished in the event of the receipt of
amendments.

(54) Title: AXIAL COOLING TUBES PROVIDED WITH CLAMPING MEANS

(57) Abstract

A rotating electric machine, comprising a stator (1) wound with high-voltage cable and provided with stator teeth (4) extending radially inwards from an outer yoke portion (23), wherein at least one stator tooth (4) in a tooth sector (18) is provided with at least one axially-running cooling duct (24) connected to a cooling circuit (25) in which coolant is arranged to circulate and in that the axially-running cooling tube (24) is connected at least at one end of the stator (1) to a clamping means (27, 28) for axial compression of the stator (1).



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav	TM	Turkmenistan
BF	Burkina Faso	GR	Greece		Republic of Macedonia	TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's	NZ	New Zealand		
CM	Cameroon		Republic of Korea	PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

AXIAL COOLING TUBES PROVIDED WITH CLAMPING MEANS

TECHNICAL FIELD:

The present invention relates to rotating electric machines such as
5 synchronous machines. Such machines can be used as generators for
connection to the distribution or transmission power network, hereafter
called power network. The invention also comprises double-fed machines,
applications in asynchronous static current converter cascades, outer pole
10 machines and synchronous flux machines, as well as alternating current
machines. The invention relates particularly to a clamping means and
with the clamping means combined cooling system of such machines.

BACKGROUND ART:

High-voltage rotating electric machines can be
15 designed for voltages up to 36 kV. This has normally been considered to
be an upper limit. In the case of generators, this means that a generator
must be connected to the power network via a transformer which steps up
the voltage to the level of the power network. The voltage of a power
network can be in the range of 130-400 kV, but even power networks up
20 to 800 kV exist.

In order to explain and describe the invention a short explanation of a
rotating electric machine exemplified by a synchronous machine will be
given. The explanation concern basically the magnetic circuit in such a
25 machine and how it is classically built. Since the magnetic circuit as
referred to in most cases is in the stator the magnetic circuit here referred
to is called a stator comprising laminated sheets which winding is called
stator winding and that the slots for the winding in the laminated sheets is
called stator slots or simply slots.

30 Most synchronous machines have a field winding in the rotor, where the
main flux is generated by direct current, and an alternating current
winding in the stator.

35 The stator frame in large sized synchronous machines is often a welded
construction. The laminated core is usually built from varnished 0,35 or

0,5 mm electrical steel. The sheets are manufactured in segmented form or ring form depending on the size of the machine. The sheets are in larger machines punched in segments which are attached to the stator frame with wedges/dovetails. The laminated core is kept together with pressure fingers and pressure rings.

For cooling the windings of the synchronous machine there exist three different types of cooling systems. In air-cooling, the winding of the stator as well as the winding of the rotor is cooled by air flowing through the windings. Air-cooling ducts are arranged in the laminated sheets of the stator as well as in the rotor. In radial ventilation and cooling by air the laminated core is, at least for medium sized and large sized machines divided in packets comprising radial and axial ventilation ducts disposed in the core. The cooling air can be ambient air but at powers above 1 MW mainly a closed cooling system with a heat exchanger is used. Hydrogen cooling is normally used in large turbo-generators and in large synchronous compensators. The cooling method works in the same way as in air-cooling with a heat exchanger, but instead of air as cooling medium hydrogen is used. Hydrogen has better cooling capabilities than air, but difficulties arise at sealings and to detect leakage. In turbo-generators of power range 500 - 1000 MW it is also known to use water cooling of the winding of the stator as well as of the winding of the rotor. The cooling ducts are made as tubes placed inside conductors in the winding of the stator. A problem in large machines is that the cooling tends to become non-uniform and that temperature variations arise in the machine.

The stator winding is located in slots in the sheet iron core, the slots normally having a rectangular or trapezoidal cross section. Each winding phase comprises a number of coil groups connected in series and each coil group comprises a number of coils connected in series. The different parts of the coil are designated coil side for the part which is placed in the stator and end winding for that part which is located outside the stator. A coil comprises one or more conductors brought together in height and/or width.

Between each conductor there is a thin insulation, for example epoxy/glass fibre.

- 5 The coil is insulated from the slot with a coil insulation, that is, an insulation intended to withstand the rated voltage of the machine to earth. As insulating material, various plastic, varnish and glass fibre materials may be used. Usually, so-called mica tape is used, which is a mixture of mica and hard plastic, especially produced to provide resistance to partial discharges, which can rapidly break down the insulation. The insulation is applied to the coil by winding the mica tape around the coil in several layers. The insulation is impregnated, and then the coil side is painted with a graphite-based paint to improve the contact with the surrounding stator which is connected to earth potential. The cross-sectional area of the windings is determined by actual current density and by the method of cooling. Conductor and coil is usually arranged with a rectangular shape in order to maximize the amount of conductor material in the track. A typical coil is formed by so called Roebel-bars, where some of the conductors can be made hollow for cooling medium. A Roebel-bar contains several rectangular, copper conductors connected in parallel, which are transposed 360 degrees along the slot. Known are also annular bars with 540 degrees transpositions. The transpositions are performed in order to avoid the development of circulating currents in the cross-section of the conductor material as seen from the magnetic field.
- 25 Due to mechanical and electrical reasons there are certain upper limits which a machine cannot exceed. The power of the machine is determined mainly by three factors:
- The cross-sectional area of the windings. At normal working temperature copper has a maximum value of 3-3,5 A/mm².
 - 30 - Maximum magnetic flux density in the material of the stator and the rotor.
 - Maximum electric-field strength in the insulating material, the so-called dielectric strength.
- 35 It is considered that coils for rotating generators can be manufactured with good results within a voltage range of 3 - 25 kV.

Attempts to develop the generator for higher voltages however, have been in progress for a long time. This is obvious, for instance from "Electrical World", October 15, 1932, pages 524-525. This describes how a generator designed by Parson 1929 was arranged for 33 kV. It also describes a
5 generator in Langerbrugge, Belgium, which produced a voltage of 36 kV. Although the article also speculates on the possibility of increasing voltage levels still further, the development was curtailed by the concepts upon which these generators were based. This was primarily because of the shortcomings of the insulation system where varnish-impregnated
10 layers of mica oil and paper were used in several separate layers.

In a report from the Electric Power Research Institute, EPRI, EL-3391 from April 1984, an account is given of generator concepts for achieving higher voltage in an electric generator with the object of being able to connect
15 such a generator to a power network without intermediate transformers. Such a solution is assessed in the report to offer good gains in efficiency and considerable financial advantages. The main reason that it was deemed possible in 1984 to start developing generators for direct connection to power networks was that a superconducting rotor had been
20 developed at that time. The considerable excitation capacity of the superconducting field winding enables the use of airgap-winding with sufficient thickness to withstand the electrical stresses.

By combining the concept deemed most promising according to the project, that of designing a magnetic circuit with winding, known as
25 "monolithic cylinder armature", a concept in which two cylinders of conductors are enclosed in three cylinders of insulation and the whole structure is attached to an iron core without teeth, it was assessed that a rotating electric machine for high voltage could be directly connected to a power network. The solution entailed the main insulation having to be
30 made sufficiently thick to withstand network-to-network and network-to-earth potentials. Obvious drawbacks with the proposed solution, besides its demanding a superconducting rotor, are that it also requires extremely thick insulation, which increases the machine size. The end windings must be insulated and cooled with oil or freones in order to control the
35 large electric fields at the ends. The whole machine must be hermetically

sealed in order to prevent the liquid dielectric medium from absorbing moisture from the atmosphere.

5 Certain attempts at a new approach as regards the design of synchronous machines are described, inter alia, in an article entitled "Water-and-oil-cooled Turbogenerator TVM-300" in J. Elektrotechnika, No. 1, 1970, pp. 6-8, in US 4,429,244 "Stator of Generator" and in Russian patent document CCCP Patent 955369.

10 The water- and oil-cooled synchronous machine described in J. Elektrotechnika is intended for voltages up to 20 kV. The article describes a new insulation system consisting of oil/paper insulation, which makes it possible to immerse the stator completely in oil. The oil can then be used as a coolant while at the same time using it as insulation. To prevent oil in
15 the stator from leaking out towards the rotor, a dielectric oil-separating ring is provided at the internal surface of the core. The stator winding is made from conductors with an oval hollow shape provided with oil and paper insulation. The coil sides with their insulation are secured to the slots made with rectangular cross section by means of wedges. As coolant,
20 oil is used both in the hollow conductors and in holes in the stator walls. Such cooling systems, however, entail a large number of connections of both oil and electricity at the coil ends. The thick insulation also entails an increased radius of curvature of the conductors, which in turn results in an increased size of the winding overhang.

25 The above-mentioned US patent relates to the stator part of a synchronous machine which comprises a magnetic core of laminated sheet with trapezoidal slots for the stator winding. The slots are tapered since the need of insulation of the stator winding is less towards the interior of the
30 rotor where that part of the winding which is located nearest the neutral point is disposed. In addition, the stator part comprises a dielectric oil-separating cylinder nearest the inner surface of the core which may increase the magnetization requirement relative to a machine without this ring. The stator winding is made of oil-immersed cables with the same
35 diameter for each coil layer. The layers are separated from each other by

means of spacers in the slots and secured by wedges. What is special regarding the winding is that it comprises two so-called half-windings connected in series. One of the two half-windings is located, centred, inside an insulation sleeve. The conductors of the stator winding are cooled by surrounding oil. The disadvantages with such a large quantity of oil in the system are the risk of leakage and the considerable amount of cleaning work which may result from a fault condition. Those parts of the insulation sleeve which are located outside the slots have a cylindrical part and a conical termination reinforced with current-carrying layers, the duty of which is to control the electric field strength in the region where the cable enters the end winding.

From CCCP 955369 it is clear, in another attempt to raise the rated voltage of the synchronous machine, that the oil-cooled stator winding comprises a conventional high-voltage cable with the same dimension for all the layers. The cable is placed in stator slots formed as circular, radially disposed openings corresponding to the cross-section area of the cable and the necessary space for fixing and for coolant. The different radially disposed layers of the winding are surrounded by and fixed in insulated tubes. Insulating spacers fix the tubes in the stator slot. Because of the oil cooling, an internal dielectric ring is also needed here for sealing the coolant against the internal air gap. The design shown has no tapering of the insulation or of the stator slots. The design exhibits a very narrow radial waist between the different stator slots, which means a large slot leakage flux which significantly influences the magnetization requirement of the machine.

In US 4,208,597 an improved cooling is provided for the end region of a stator core of a large dynamoelectric machine showing an improved ventilation plate which can be used in direct contact with the finger plate at the end of the stator core to provide cooling and mechanical stability in the core end region. US 4,745,314 shows a liquid-cooled motor which has cooled liquid ducts formed in the laminated core of the stator. This improves the leakproof performance of the coolant ducts of such a liquid-cooled motor. US 5,365,132 shows an improved cooling arrangement for a dynamoelectric machine of the type having a plurality of stacked

laminations forming a stator core. The arrangement is further showing a plurality of cooling air ducts formed in the lamination adjacent a radially outer termination of at least some of the winding slots. EP 0684682 shows a rotating electrical machine with openings in its stator teeth occupying a substantial part of the surface area of each tooth so that the stator windings have only a short thermal path to axial cooling ducts created by the openings.

OBJECT OF THE INVENTION:

The object of the present invention is to mechanically connect layers of the sheets of the stator so that the packets of layers defining the stator core will not be exposed to vibrations under working conditions. The connection will also be made so that the mechanical properties of the core is intact.

An other object of the invention is to combine the connection of the sheets into packet of layers with cooling of the core.

A condition for the invention is that the rotating electric machine should shows a complete new design. This new design involves construction of the rotating electric machine in a way so that its alternating current winding comprises at least one conductor, around which a solid isolation comprising a semiconducting layer near the conductor and an outer semiconducting layer around the insulator.

A rotating electric machine as presented shows many advantages and can be designed for direct connection to a power network without a transformer therebetween.

The connection of the laminated sheets is done by axial clamping means which are electrically insulated from the layers of laminated sheets. The insulation can be made by coating the clamping means with an outer insulating layer or by manufacturing the clamping means of insulation material. The clamping means are pulled through axial holes in the stator teeth and also through holes in the connecting part of the stator, the so-called stator yoke if necessary.

SUMMARY OF THE INVENTION:

The present invention relates to an arrangement for cooling and a clamping means combined with the cooling arrangement, which enable
5 compression of the laminations in the stator stack with the aid of cooling tubes arranged axially in the stator.

The arrangement comprises axially-running tubes, electrically insulated, which are drawn through axial apertures through the stator teeth. The
10 tubes are permanently glued in the apertures to ensure good cooling capacity when coolant is circulated in the tubes. The tubes run along the entire axial length of the stator teeth and are spliced in the stator ends.

According to a particularly preferred embodiment of the invention, at
15 least one of the semiconducting layers, preferably both, have the same coefficient of thermal expansion as the solid insulation. The decisive benefit is thus achieved that defects, cracks or the like are avoided at thermal movement in the winding.

20 BRIEF DESCRIPTION OF THE DRAWINGS:

The invention will be described in more detail with reference to the accompanying drawings.

- Figure 1 shows schematically a perspective view of a section taken
25 diametrically through the stator of a rotating electrical machine.
- Figure 2 shows a cross-sectional view of a high-voltage cable according to the present invention,
- Figure 3 shows schematically one sector of a rotating electric machine,
- 30 Figure 4 shows a sector of a stator according to Figure 3,
- Figure 5 shows section along the line A-A in Figure 4 with a clamping means having axial cooling tubes in accordance with the present invention.
- Figure 6 shows one sector of the stator in a rotating electric machine
35 with cooling tubes and bolts drawn in.

Figure 7 shows a radial section B-B through Figure 6 with a clamping device with bolts according to the present invention

Figure 8 shows another radial section with axially running cooling-tube loops and a clamping device according to the invention.

5

DESCRIPTION OF THE INVENTION:

Figure 1 shows a part of an electric machine in which the rotor has been removed to show more clearly the arrangement of a stator 1. The main parts of the stator 1 constitute a stator frame 2, a stator core 3 comprising stator teeth 4 and a stator yoke 5. The stator also comprises a stator winding 6 composed of high-voltage cable situated in a space 7 shaped like a bicycle chain, see Figure 3, formed between each individual stator tooth 4. In Figure 3 the stator winding 6 is only indicated by its electric conductors. As can be seen in Figure 1, the stator winding 6 forms an end-winding package 8 on both sides of the stator 1. It is also clear from Figure 3 that the high-voltage cable has several dimensions, arranged in groups depending on the radial position of the cables in the stator 1.

In large machines each stack of laminations is formed by fitting punched segments 9 of suitable size together to form a first layer, after which each subsequent layer is placed at right angles to produce a complete plate-shaped part of a stator core 3. The parts are held together by pressure legs 10 pressing against pressure rings, fingers or segments.

Figure 2 shows a cross-sectional view of a high-voltage cable 11 according to the invention. The high-voltage cable 11 comprises a number of strands 12 of copper (Cu), for instance, having circular cross section. These strands 12 are arranged in the middle of the high-voltage cable 11. Around the strands 12 is a first semiconducting layer 13, and around the first semiconducting layer 13 is an insulating layer 14, e.g. crosslinked polyethylene (XLPE) insulation. Around the insulating layer 14 is a second semiconducting layer 15. Thus the concept "high-voltage cable" in the present application does not include the outer protective sheath that normally surrounds such cables for power distribution.

35

Figure 3 shows schematically a radial sector of a machine with a segment 9 of the stator 1 and with a rotor pole 16 on the rotor 17 of the machine. It can also be seen that the stator winding 6 is arranged in the space 7 resembling a bicycle chain, formed between each stator tooth 4.

5

Figure 4 shows an outermost tooth sector 18 comprising six stator teeth 4, four of which in the figure are provided with a pressure finger 19 extending from the stator yoke 5 in towards the tip 20 of the stator tooth.

- 10 The tooth height is defined as the radial distance from the tip 20 of a tooth to the outer end 21 of the space 7 resembling a bicycle chain. The length of a stator tooth is thus equivalent to the tooth height. Furthermore, the yoke height is defined as the radial distance from the outer end 21 of the space 7 resembling a bicycle chain, to the outer edge 22 of the stator core. This
- 15 latter distance denotes the width of an outer yoke portion 23.

- In a high-voltage rotating electric machine of the type described above at least one stator tooth 4 is provided according to the present invention, see Figure 4, with at least one axially-running cooling tube 24 connected to a
- 20 cooling circuit 25 in which coolant is arranged to circulate. To achieve efficient cooling, cooling tubes are preferably arranged in every stator tooth. According to the embodiment of the invention shown in Figure 4 four cooling tubes are arranged to run axially through the actual tooth, whereas another two cooling tubes are arranged to run axially through the
- 25 outer yoke portion 23 of the sector shown. All cooling tubes in the figure shown are also radial aligned.

- Each cooling tube 24 is electrically insulated and provided with an insulating layer, not shown, in order to avoid contact with the metal in the
- 30 stator tooth 4 or in the outer yoke portion 23. A thermally conducting glue may alternatively be used for attachment.

- Figure 5 shows a clamping means according to one embodiment of the invention in which the cooling tube 24 extends out through a stator 3 built up of segments 9. The tube is provided with an insulating layer 26,
- 35 possibly combined with a filling to increase thermal conductivity. The

cooling tube 24 is provided at its end with a tapped end portion 27 onto which a nut 28 can be screwed. The end portion 27 extends through the pressure finger 19. The end part is also provided with an insulating washer 29 to insulate it from the stator core 3 and the pressure finger 19.

- 5 The end part is also provided with a tube connection 30 to connect the end portion with a connection cooling tube 31 connected to the cooling circuit 25, for instance.

- 10 By tightening the nut 28 against the insulating washer 29 and the pressure finger 19, an axial compressive force is achieved in the cooling tube 24 which is drawn towards a counter-support on the other side of the stator, or another clamping means of the same type. Alternatively clamping can be effected against a shoulder 32 secured to the cooling tube 24. Pressure fingers 19 are also provided at this second side. Here, too, pressure fingers
15 and cooling tubes are of course insulated here, too, from the stator core by suitably shaped washers 33, etc.

Thus by using an axial cooling tube as a pulling tube, further clamping means for axially compressing the stator core can be eliminated.

20

The invention is not limited to the embodiments shown but is defined by the appended claims. Thus types of clamping means other than screw joints may be used, such as wedge or spring means, etc.

- 25 Figure 6 shows like in figure 4 an outermost tooth sector 118 comprising six stator teeth 104, four of which in the figure are provided with a pressure finger 119 extending from the stator yoke 105 in towards the tip 120 of the stator tooth.

- 30 The tooth height is defined as the radial distance from the tip 120 of a tooth to the outer end 121 of the space 107 resembling a bicycle chain. The length of a stator tooth is thus equivalent to the tooth height. Furthermore, the yoke height is defined as the radial distance from the outer end 121 of the space 107 resembling a bicycle chain, to the outer edge 122 of the stator
35 core. This latter distance denotes the width of an outer yoke portion 123.

In a high-voltage rotating electric machine of the type described above at least one stator tooth 104 is provided according to the present invention, see Figure 6, with at least one axially-running cooling tube 124 connected to a cooling circuit 125 in which coolant is arranged to circulate. To
5 achieve efficient cooling, cooling tubes are preferably arranged in every stator tooth. According to the embodiment of the invention shown in Figure 6 four cooling tubes are arranged to run axially through the actual tooth, whereas one more cooling tube is arranged to run axially through the outer yoke portion 123 of the sector shown. All cooling tubes in the
10 figure shown are also radially aligned. Each cooling tube 124 is electrically insulated and provided with an insulating layer, not shown, in order to avoid contact with the metal in the stator tooth 104 or in the outer yoke portion 123. A thermally conducting glue may alternatively be used for attachment.

15 The Figure also shows how a clamping device is placed between the cooling tubes as a first possible embodiment, and between the windings as a second possible embodiment. Figure 7 shows a clamping device according to one embodiment of the invention in which one or more axial
20 clamping devices are placed between each cooling tube 124 according to one embodiment of the invention, see also Figure 6, in the magnetic material in the form of either insulated metal bolts or glass fibre bolts which are insulating per se. The clamping device 126 is provided at both ends with an end portion 127, preferably threaded, onto which a nut 128
25 can be screwed. The end portion 127 extends through the pressure finger 119. The end part is also provided with spring means 129, shown in the Figure as a plate spring, to take up axial fluctuations in the stator 1 caused by temperature. Some form of spring means is required to take up
30 longitudinal expansion caused by heat transfer, which the pre-stressing is unable to deal with. The stator shall be permanently axially pre-stressed.

By tightening the end part with a nut 128, for instance, towards the spring means 129 and the pressure finger 119, an axial compressive force is
35 achieved in the clamping device 126 which is drawn towards a counter-support or a similar tension device on the other side of the stator. Here, too, pressure fingers and cooling tubes are of course insulated from the

stator core by suitably shaped washers , etc., not shown. In another advantageous embodiment, the clamping device 126 is disposed in the space 107 (slot) shaped like a bicycle chain, see Figure 7, in the space between the stator windings 106, i.e. outside the magnetic material.

5

Figure 8 shows a clamping device 126 in a radial section through a stator tooth, together with the cooling tubes 124 running axially to and fro.

Together with the clamping device, a clamping yoke 130 provided with axially operating pressure fingers 131 effects an axial force compressing
10 the stack of laminations.

The invention is not limited to the embodiments shown but is defined by the appended claims. Cooling tubes and clamping devices need not be radially aligned, for instance but their placing in tangential direction may
15 vary instead.

CLAIMS

1. A high-voltage rotating electric machine, comprising a magnetic core built of laminated steel and a winding placed in slots in the core of laminated steel, characterized in that the winding comprises an insulation system including at least two semiconducting layers, each layer constituting essentially an equipotential surface and also including solid isolation disposed therebetween and that a clamping device is extending axially from the laminated steel and arranged for holding a packet of sheets together and whereby at least one end of the core of the laminated steel is connected to at least one clamping device for axially pressing a packet of sheets together at a predetermined amount of tension.
2. A machine as claimed in claim 1, characterized in that the clamping device is extending axially through the magnetic core.
3. A machine as claimed in any of claim 1-2, characterized in that the axially extending clamping device is arranged with an inner space for circulating coolant.
4. A rotating electric machine, comprising a stator (1) wound with high-voltage cable and provided with stator teeth (4) extending radially inwards from an outer yoke portion (23), characterized in that at least one stator tooth (4) in a tooth sector (18) is provided with at least one axially-running cooling duct (24) connected to a cooling circuit (25) in which coolant is arranged to circulate and in that the axially-running cooling tube (24) is connected at least at one end of the stator (1) to a clamping means (27, 28) for axial compression of the stator (1).
5. A machine as claimed in claim 4, characterized in that the clamping means (27, 28) comprises at least one screw joint arranged, with the cooling tube (24), to axially clamp the laminations together.
6. A machine as claimed in either of claims 4 or 5, characterized in that at one side of the stator (1) the cooling

tube (24) is provided with a firmly secured shoulder (32) and at the other side of the stator it is provided with a clamping means (27, 28) to axially clamp the stator laminations together.

5 7. A machine as claimed in claim 6, characterized in that the clamping means (27, 28) also acts against a pressure finger (19) for axial clamping of the stator laminations.

8. A machine as claimed in claim 7, characterized in
10 that the clamping means (27, 28) is electrically insulated from the stator core (3).

9. A machine as claimed in claim 8, characterized in
that the cooling tubes (24) are glued to the stator core (3).

15

10. A rotating electric machine comprising a wound stator (1) consisting of stator laminations and provided with stator teeth (104) extending radially inwards from an outer yoke portion (123),
characterized in that an axially running clamping device
20 electrically insulated from the stator laminations is connected at least at one end of the stator (1) to at least one clamping device (126) for axial compression to predetermined pre-stressing of the stator (1).

11. A machine as claimed in claim 10, characterized in
25 that the stator winding consists of high-voltage cable (11).

12. A machine as claimed in either of claims 10 or 11,
characterized in that the clamping device (126) runs axially
through the magnetic material of the stator (1).

30

13. A machine as claimed in either of claims 10 or 11,
characterized in that the clamping device (126) runs between
the high-voltage cables (11) in the space (107) formed between two
adjacent stator teeth (104).

35

14. A machine as claimed in any of claims 10-13, characterized in that the entire clamping device (126) is made of an insulating material, preferably glass fibre.
- 5 15. A machine as claimed in any of claims 10-13, characterized in that the clamping device (126) is arranged as a metallic pipe electrically insulated from the laminations of the stator (1).
- 10 16. A machine as claimed in either of claims 14 or 15, characterized in that the clamping device (126) is arranged to pre-stress the stator (1) with at least one spring device (129).
- 15 17. A machine as claimed in either of claims 14 or 15, characterized in that the clamping device (126) is arranged to pre-stress the laminated stack against the action of a rubber spring.
18. A machine as claimed in any of claims 10-17, characterized in that several clamping devices (126) are arranged in at least one stator tooth (104) so that each cooling tube (124) is
20 flanked by an axially extending clamping device (126).
19. A machine as claimed in any of claims 10-18, characterized in that an additional clamping device (126) also runs through the yoke portion (123).
25
20. A machine as claimed in any of claims 10-19, characterized in that clamping devices (126) and cooling tubes (124) are arranged radially aligned.
- 30 21. A machine as claimed in any of claims 1-3, characterized in that at least one of the layers has substantially the same coefficient of thermal expansion as the solid insulation.
- 35 22. A machine as claimed in any of the preceding claims, characterized in that said winding is formed of a cable comprising one or more current-carrying conductors, each conductor

having a number of strands, an inner semiconducting layer provided around each conductor, an insulating layer of solid insulating material provided around said inner semiconducting layer, and an outer semiconducting layer provided around said insulating layer.





Fig. 3



2/4

Fig. 4





Fig. 5
A-A






Fig. 6




Fig. 7




Fig. 8

INTERNATIONAL SEARCH REPORT

International application No.

PCT/SE 97/00895

A. CLASSIFICATION OF SUBJECT MATTER

IPC6: H02K 1/20, H02K 3/40, H02K 15/08

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC6: H02K

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

SE,DK,FI,NO classes as above

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

WPI

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	US 5036165 A (R.K. ELTON ET AL), 30 July 1991 (30.07.91), see the whole document --	1-2,21-23
Y	US 4853565 A (R.K.ELTON), 1 August 1989 (01.08.89), column 5, line 55 - line 61; column 7, line 12 - line 37, figures 4,7 --	1-2,21-23
Y	US 4208597 A (A.MULACH ET AL.), 17 June 1980 (17.06.80), see the whole document	1-2,21-23
X		10-20
A		3,4-9
	--	

☒ Further documents are listed in the continuation of Box C.☒ See patent family annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

29 Sept. 1997

Date of mailing of the international search report

07-10-1997

Name and mailing address of the ISA/

Swedish Patent Office

Box 5055, S-102 42 STOCKHOLM

Facsimile No. +46 8 666 02 86

Authorized officer

Lars Jakobsson

Telephone No. +46 8 782 25 00

INTERNATIONAL SEARCH REPORT

International application No.

PCT/SE 97/00895

C (Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	US 5365132 A (J.C.HANN ET AL), 15 November 1994 (15.11.94), se the whole document	1-2,21-23
X		10-20
A		3,4-9
	--	
Y	US 4745314 A (J.NAKANO), 17 May 1988 (17.05.88)	1-2,21-23
X		10-20
A		3,4-9
	--	
A	EP 0684682 A1 (GEC ALSTHOM LTD.), 29 November 1995 (29.11.95), see the whole document	4-9
	--	
A	US 3801843 A (J.C.CORMAN ET AL), 2 April 1974 (02.04.74), see the whole document	4-9
	-- -----	

INTERNATIONAL SEARCH REPORT

International application No.

PCT/SE 97/00895

Box I Observations where certain claims were found unsearchable (Continuation of Item 1 of first sheet)

This international search report has not been established in respect of certain claims under Article 17(2)(a) for the following reasons:

1. ☐ Claims Nos.:
because they relate to subject matter not required to be searched by this Authority, namely:
2. ☐ Claims Nos.:
because they relate to parts of the international application that do not comply with the prescribed requirements to such an extent that no meaningful international search can be carried out, specifically:
3. ☐ Claims Nos.:
because they are dependent claims and are not drafted in accordance with the second and third sentences of Rule 6.4(a).

Box II Observations where unity of invention is lacking (Continuation of Item 2 of first sheet)

This International Searching Authority found multiple inventions in this international application, as follows:

Claim 1: An electric machine comprising a winding with semiconducting layers and a clamping device.

Claim 4: An electric machine with a cooling tube in a stator tooth where the cooling tube is connected to a clamping means.

Claim 10: An electric machine with a clamping device.

Claims 4 and 10 have no special technical features in common.

1. ☐ As all required additional search fees were timely paid by the applicant, this international search report covers all searchable claims.
2. ☒ As all searchable claims could be searched without effort justifying an additional fee, this Authority did not invite payment of any additional fee.
3. ☐ As only some of the required additional search fees were timely paid by the applicant, this international search report covers only those claims for which fees were paid, specifically claims Nos.:
4. ☐ No required additional search fees were timely paid by the applicant. Consequently, this international search report is restricted to the invention first mentioned in the claims; it is covered by claims Nos.:

Remark on Protest

- ☐ The additional search fees were accompanied by the applicant's protest.
☐ No protest accompanied the payment of additional search fees.

INTERNATIONAL SEARCH REPORT
Information on patent family members

01/09/97

International application No.
PCT/SE 97/00895

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 5036165 A	30/07/91	US 5066881 A US 5067046 A CA 1245270 A US 4853565 A	19/11/91 19/11/91 22/11/88 01/08/89
US 4853565 A	01/08/89	CA 1245270 A US 5036165 A US 5066881 A US 5067046 A	22/11/88 30/07/91 19/11/91 19/11/91
US 4208597 A	17/06/80	BE 877203 A CA 1083212 A DE 2924697 A FR 2429513 A JP 55005095 A	24/12/79 05/08/80 10/01/80 18/01/80 14/01/80
US 5365132 A	15/11/94	CA 2122386 A EP 0627804 A JP 7023538 A	28/11/94 07/12/94 24/01/95
US 4745314 A	17/05/88	JP 61121729 A WO 8603069 A	09/06/86 22/05/86
EP 0684682 A1	29/11/95	CA 2148213 A FI 952501 A GB 2289992 A GB 9410351 D JP 7322565 A	25/11/95 25/11/95 06/12/95 00/00/00 08/12/95
US 3801843 A	02/04/74	CA 964710 A DE 2330172 A FR 2189915 A,B	18/03/75 03/01/74 25/01/74

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

PATENT COOPERATION TREATY

PCT

NOTIFICATION OF ELECTION

(PCT Rule 61.2)

From the INTERNATIONAL BUREAU

To:

United States Patent and Trademark
Office
(Box PCT)
Crystal Plaza 2
Washington, DC 20231
ETATS-UNIS D'AMERIQUE

in its capacity as elected Office

Date of mailing (day/month/year) 21 January 1998 (21.01.98)	
International application No. PCT/SE97/00895	Applicant's or agent's file reference P 97-124/AE
International filing date (day/month/year) 27 May 1997 (27.05.97)	Priority date (day/month/year) 29 May 1996 (29.05.96)
Applicant LEIJON, Mats et al	

1. The designated Office is hereby notified of its election made:

☒ in the demand filed with the International Preliminary Examining Authority on:
19 December 1997 (19.12.97)

☐ in a notice effecting later election filed with the International Bureau on:

2. The election ☒ was
☐ was not

made before the expiration of 19 months from the priority date or, where Rule 32 applies, within the time limit under Rule 32.2(b).

The International Bureau of WIPO 34, chemin des Colombettes 1211 Geneva 20, Switzerland Facsimile No.: (41-22) 740.14.35	Authorized officer I. Britel Telephone No.: (41-22) 338.83.38
--	--

PATENT COOPERATION TREATY

PCT

COMMUNICATION OF
INTERNATIONAL APPLICATIONS

(PCT Article 20)

From the INTERNATIONAL BUREAU

To:

United States Patent and Trademark
Office
(Box PCT)
Crystal Plaza 2
Washington, DC 20231
ETATS-UNIS D'AMERIQUE

Date of mailing:

26 February 1998 (26.02.98)

in its capacity as designated Office

The International Bureau transmits herewith copies of the international applications having the following international application numbers and international publication numbers:

International application no.:

PCT/SE97/00895

International publication no.:

WO97/45916

**CORRECTED VERSION
VERSION CORRIGEE**

The International Bureau of WIPO
34, chemin des Colombettes
1211 Geneva 20, Switzerland

Facsimile No.: (41-22) 740.14.35

Authorized officer:

J. Zahra
Telephone No.: (41-22) 338.83.38

CORRECTED
VERSION*

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : H02K 1/20, 3/40, 15/08		A1	(11) International Publication Number: WO 97/45916
			(43) International Publication Date: 4 December 1997 (04.12.97)
(21) International Application Number: PCT/SE97/00895		(74) Agent: EMTEDAL, Artur; L.A. Groth & Co. KB, P.O. Box 6107, S-102 32 Stockholm (SE).	
(22) International Filing Date: 27 May 1997 (27.05.97)			
(30) Priority Data: 9602079-7 29 May 1996 (29.05.96) SE 9602089-6 29 May 1996 (29.05.96) SE 9700351-1 3 February 1997 (03.02.97) SE			
(71) Applicant (for all designated States except US): ASEA BROWN BOVERI AB [SE/SE]; S-721 83 Västerås (SE).			
(72) Inventors; and			
(75) Inventors/Applicants (for US only): LEIJON, Mats [SE/SE]; Hyvlargatan 5, S-723 35 Västerås (SE). LARSSON, Bertil [SE/SE]; Sammetvägen 12, S-724 76 Västerås (SE). KYLANDER, Gunnar [SE/SE]; Stentorpsgatan 16 A, S-723 43 Västerås (SE). BERGGREN, Sören [SE/SE]; Vetterstorgsgatan 30, S-724 62 Västerås (SE). ROTHMAN, Bengt [SE/SE]; Profilgatan 16, S-723 36 Västerås (SE). JONAS, Ivan [SE/SE]; Hermods väg 9, S-723 55 Västerås (SE). EDMAN, Arne [SE/SE]; Gudrunsväg 12, S-723 55 Västerås (SE). HYLANDER, Jonny [SE/SE]; Öjenås, S-510 13 Björketorp (SE).			
		(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, CZ (Utility model), DE, DE (Utility model), DK, DK (Utility model), EE, ES, FI, FI (Utility model), GB, GE, GH, HU, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ARIPO patent (GH, KE, LS, MW, SD, SZ, UG), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).	
		Published With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.	

(54) Title: AXIAL COOLING TUBES PROVIDED WITH CLAMPING MEANS

(57) Abstract

A rotating electric machine, comprising a stator (1) wound with high-voltage cable and provided with stator teeth (4) extending radially inwards from an outer yoke portion (23), wherein at least one stator tooth (4) in a tooth sector (18) is provided with at least one axially-running cooling duct (24) connected to a cooling circuit (25) in which coolant is arranged to circulate and in that the axially-running cooling tube (24) is connected at least at one end of the stator (1) to a clamping means (27, 28) for axial compression of the stator (1).




PATENT COOPERATION TREATY

PCT

INTERNATIONAL PRELIMINARY EXAMINATION REPORT

(PCT Article 36 and Rule 70)



Applicant's or agent's file reference P 97-124/AE/PA	FOR FURTHER ACTION See Notification of Transmittal of International Preliminary Examination Report (Form PCT/IPEA/416)	
International application No. PCT/SE97/00895	International filing date (day/month/year) 27.05.1997	Priority date (day/month/year) 29.05.1996
International Patent Classification (IPC) or national classification and IPC ₆ H 02 K 1/20, H 02 K 3/40, H 02 K 15/08		
Applicant Asea Brown Boveri AB et al.		

1.	This international preliminary examination report has been prepared by this International Preliminary Examining Authority and is transmitted to the applicant according to Article 36.
2.	This REPORT consists of a total of <u>4</u> sheets, including this cover sheet.
	<input checked="" type="checkbox"/> This report is also accompanied by ANNEXES, i.e., sheets of the description, claims and/or drawings which have been amended and are the basis for this report and/or sheets containing rectifications made before this Authority (see Rule 70.16 and Section 607 of the Administrative Instructions under the PCT).
	These annexes consist of a total of <u>3</u> sheets.
3.	This report contains indications relating to the following items:
	I <input checked="" type="checkbox"/> Basis of the report
	II <input type="checkbox"/> Priority
	III <input type="checkbox"/> Non-establishment of opinion with regard to novelty, inventive step and industrial applicability
	IV <input type="checkbox"/> Lack of unity of invention
	V <input checked="" type="checkbox"/> Reasoned statement under Article 35(2) with regard to novelty, inventive step or industrial applicability; citations and explanations supporting such statement
	VI <input type="checkbox"/> Certain documents cited
	VII <input type="checkbox"/> Certain defects in the international application
	VIII <input type="checkbox"/> Certain observations on the international application

Date of submission of the demand 19.12.1997	Date of completion of this report 02.10.1998
Name and mailing address of the IPEA/SE Patent- och registreringsverket Box 5055 S-102 42 STOCKHOLM Facsimile No. 08-667 72 88	Authorized officer Lars Jakobsson Telephone No. 08-782 25 00

INTERNATIONAL PRELIMINARY EXAMINATION REPORT

International application No.

PCT/SE97/00895

I. Basis of the report

1. This report has been drawn on the basis of (Replacement sheets which have been furnished to the receiving Office in response to an invitation under Article 14 are referred to in this report as "originally filed" and are not annexed to the report since they do not contain amendments.):

- ☐ the international application as originally filed.
- ☒ the description, pages 1-13, as originally filed,
pages _____, filed with the demand,
pages _____, filed with the letter of _____,
pages _____, filed with the letter of _____.
- ☒ the claims, Nos. _____, as originally filed,
Nos. _____, as amended under Article 19,
Nos. _____, filed with the demand,
Nos. 1-22, filed with the letter of 29.09.1998,
Nos. _____, filed with the letter of _____.
- ☒ the drawings, sheets/fig 1-8, as originally filed,
sheets/fig _____, filed with the demand
sheets/fig _____, filed with the letter of _____,
sheets/fig _____, filed with the letter of _____.

2. The amendments have resulted in the cancellation of:

- ☐ the description, pages _____
- ☐ the claims, Nos. _____
- ☐ the drawings, sheets/fig _____

3. ☐ This report has been established as if (some of) the amendments had not been made, since they have been considered to go beyond the disclosure as filed, as indicated in the supplemental Box (Rule 70.2(c)).

4. Additional observations, if necessary:

INTERNATIONAL PRELIMINARY EXAMINATION REPORT

International application No.

PCT/SE97/00895

V. Reasoned statement under Article 35(2) with regard to novelty, inventive step or industrial applicability; citations and explanations supporting such statement

1. Statement

Novelty (N)	Claims	<u>1-22</u>	YES
	Claims		NO
Inventive step (IS)	Claims	<u>1-22</u>	YES
	Claims		NO
Industrial applicability (IA)	Claims	<u>1-22</u>	YES
	Claims		NO

2. Citations and explanations

Documents cited in the International Search Report:

- (A) US 5036165
- (B) US 4853565
- (C) US 4208597
- (D) US 5365132
- (E) US 4745314
- (F) EP 0684682
- (G) US 3801843

The invention relates to a high-voltage rotating electric machine. The winding of the machine is provided with an insulation system comprising two semiconducting layers with solid insulation in-between and a clamping device pressing a packet of sheets together. The invention also relates to a rotating electric machine with a high-voltage cable and a cooling tube connected to a clamping means.

(A) describes a cable provided with two semiconducting layers with insulation there between. The semiconducting layers include pyrolyzed organic material and glass fibre. In this document it is suggested that the invented semiconducting layer can be applied to insulated conductors such as a winding in a dynamo-electric machine.

(B) is a document related by reference to document (A) and illustrate a semiconducting layer in intimate contact on an outer or inner surface of an insulation on a conventional winding in an electric machine. This document also describes the cable as in document (A).

(C) - (G) describes cooling arrangements for rotating electric machines.

.../...

INTERNATIONAL PRELIMINARY EXAMINATION REPORT

International application No.

PCT/SE97/00895

Supplemental Box

(To be used when the space in any of the preceding boxes is not sufficient)

Continuation of: BOX V.

The claimed invention differs from the cited art in that the winding of the machine is provided with an insulation system comprising two semiconducting layers with solid insulation-between. The claimed invention (claims 4-9) also differs from the cited art in that a cooling tube is connected to a clamping means.

Even though it is suggested in document (A) to apply a semiconducting layer to a winding in a dynamo-electric machine there is no specific indication of using the disclosed cable in a dynamo-electric machine. Further investigating US 4853565, incorporated by reference in document (A), the skilled person will find it evident that the invented semiconducting layer is intended to be used on a conventional winding in a machine or in a cable. There is no proposal to use the cable with the insulating system as a winding in an electric machine. Nor can it be considered obvious to a person skilled in the art to use such a cable in a dynamo-electric machine since at the time of the invention it was not known to use a cable with solid insulation as a winding in an electrical machine and there is no teaching in prior art as a whole that would lead the skilled person to the claimed invention.

Accordingly, the invention claimed is novel and involves an inventive step. The invention is industrially applicable.